

NANOFABRICATION OF SILICON METASURFACES FOR THIRD HARMONIC GENERATION

Luca Fagiani^{1*}, Erfan Mafakheri¹, Kirill Okhlopkov², Andrea Tognazzi³, Attilio Zilli⁴, Michele Celebrano⁴, Maxim Shcherbakov², Andrey Fedyanin², Davide Rocco³, Marco Finazzi⁴, Costantino De Angelis³, Monica Bollani¹

1 IFN-CNR, LNESS laboratory, via Anzani 42, 22100 Como, Italy

2 Faculty of Physics, Lomonosov Moscow State University, Moscow 119991, Russia

3 Department of Information Engineering, University of Brescia, Via Branze 38, 25123 Brescia, Italy

4 Physics Department, Politecnico di Milano, Piazza Leonardo Da Vinci 32, 20133 Milano, Italy.

[*luca.fagiani@polimi.it](mailto:luca.fagiani@polimi.it)

We realized high quality silicon metasurfaces by e-beam lithography for controlling the spatial intensity distribution, polarization, and wavelength dependence of light beams generated by third-order nonlinearities.

Keywords: Metasurfaces, Third harmonic generation

Nonlinear optical processes have been studied in different materials and structures [1-2]. These processes, such as second and third harmonic generation, can find numerous applications in photonics, material science and biomedical sensing [3-4]. In this frame, metasurfaces offer promising possibilities for the miniaturization of optical devices working at visible and infrared wavelengths. Recently, dielectric and semiconductor metasurfaces with a high refractive index have emerged as a new class of engineered nanostructures for nonlinear applications, thanks to their low dissipative losses and high nonlinear susceptibilities [5-6]. In this work, we demonstrate the nanofabrication of high quality silicon metasurfaces, exploiting the easy integration of this material in nanophotonic platforms, for controlling the spatial intensity distribution, polarization, and wavelength dependence of light beams generated by third-order nonlinearities. Periodic metasurfaces will emit THG signal in the grating modes, which are very narrow in the k space. The design of the semiconductor metasurfaces has been guided by numerical simulations to obtain the desired nonlinear optical response. The metasurfaces are realized by combining electron-beam lithography and reactive ion etching, using a silicon on insulator substrate with a device layer of 125 nm on 2 μm of buried oxide. Similar structures have been optimized also on a device layer of 145 nm. The process parameters have been optimized to obtain the desired gap and periodicity of the silicon nanostructures, as reported in Fig. 1, for either 125 nm or 145 nm devices over 100 x 100 μm^2 areas.




Fig. 1 Scanning electron micrograph of a silicon metasurface

Acknowledgements

The research activity is performed in the framework of the PRIN project (NOMEN, Nonlinear Optics with METal-less Nanoantennas and metasurfaces 2020 -2023).

References

1. Timpu, F. et al., *ACS Photonics* **4**, 76–84 (2017).
2. Zhang, R. et al., *ACS Photonics* **3**, 371–377 (2016).
3. Krasnok, A., Tymchenko, M., Alú, A., *Mater. Today* **21**, 8–21A (2018).
4. Chen, S., Li, G., Zeuner, F. et al., *Phys. Rev. Lett.* **113** (3), (2014).
5. Shcherbakov, M. R. et al., *Nano Lett.* **14**, 6488–6492 (2014).
6. Camacho-Morales, R. et al., *Nano Lett.* **16**, 7191–7197 (2016).