

SEGMENTED-WAVE ANALYSIS OF NANO-GRATINGS ON CURVED SURFACES

Muhammad Fayyaz Kashif^{1,*}, Filippo Pisano², Antonio Balena^{2,3}, Marco Pisanello², Tiziana Stomeo², Massimo De Vittorio^{2,3}, Ferruccio Pisanello², Antonella D'Orazio¹ and Marco Grande¹

¹Dipartimento di Ingegneria Elettrica e dell'Informazione, Politecnico di Bari, Bari, 70125, Italy

²Fondazione Istituto Italiano di Tecnologia, Center for Biomolecular Nanotechnologies, Arnesano (LE), 73010, Italy

³Dipartimento di Ingegneria Dell'Innovazione, Università del Salento, Lecce, 73100, Italy

*muhammadfayyaz.kashif@poliba.it

In this paper, we investigate the gold nano-gratings on curved surfaces through numerical simulations. This study can be helpful to understand curvature induced effects in plasmonic devices.

Keywords: nano-gratings, surface plasmons

1. Abstract

Fiber-optic sensors have the advantages of design flexibility, miniaturization and remote sensing capability [1]. The ability to fabricate plasmonic nanostructures on the tip of a straight or tapered optical fiber can open doors to a wide range of sensing functionalities, especially for biomedical applications such as the analysis of neural circuits [2-4].

In this scenario, we detail on a gold nano-grating on a curved surface as shown in Figure 1(a) that resembles a fiber-based sensor. Numerical simulations are performed by the well-established numerical method rigorous coupled-wave analysis (RCWA). The surface curvature can be resolved by a segmentation-based approximation technique as depicted in Figure 1(b & c) [5]. For example, Figure 2 shows reflection spectra when the segmented-wave analysis is performed on a continuum film for different curvature radii. We analyse also different types of nano-gratings arranged in both one-dimensional and two-dimensional configurations.

The results from this analysis can be helpful to understand challenges that lie in the design and fabrication of plasmonic devices with a special focus on curvature induced effects and implications.




Fig. 2 Reflection spectra from a structure shown in Fig. 1(b) at various curvature radii.

References

1. Byoungcho Lee, Sookyoung Roh & Junghyun Park, *Opt. Fiber Tech.* 15, 209–221 (2009).
2. F. Pisano, M. Pisanello *et al.*, *Nat Methods* 16, 1185–1192 (2019).
3. P. Savaliya & A. Dhawan, *Opt. Letters* 41 4582 (2016).
4. A. M. Packer, B. Roska, & M. Häusser, *Nat. Neurosci.*, 16(7), 805–815 (2013).
5. H. Lee & D. Kim, *Opt. Express* 24(11), (2016).




Fig. 1 (a) Schematic of a gold nano-grating on a curved surface. (b) Continuum gold film on a curved surface and (c) segmentation-based approximation of the structure in (b). θ_{in} is the impinging angle and R is the radius of curvature.